

Product Code: SCONTDC300W

Description: Acrylic Decorators Caulk (C3) Cartridge - White



Benefits

- Paintable with water based and synthetic paints
- Perfect adhesion without primer on most surfaces
- Almost odourless
- Easy to apply
- Easy to clean
- Non corrosive towards metals

Colour White

Application

Sealing and filling of interior gaps and cracks where movement can occur, such as those between skirting boards, ceilings, architraves, plasterwork, window and door frames. Use prior to painting or papering to prevent unsightly cracks developing later.

Directions Of Use

Cut the cartridge seal and screw on the nozzle which should be cut to your required size. Using a skeleton gun, apply the sealant into the gap or joint ensuring a good solid fill.

Limitations

Not suitable for continuous exposure to water
Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates

Paintability

Can be over painted with most emulsion and oil based paints when cured. For optimum results allow 24 hours drying before painting. Use product prior to painting or papering to prevent unsightly cracks developing later. Painting over with highly filled emulsion paint can cause cracks in the paint surface.

Cleaning

Tools to be cleaned after use with water. Hands can be cleaned with SX Multi-Purpose Cleaning Wipes and/or water and soap.

Additional Information

Application Rate	@ Ø3mm/4 bar	2200 g/min
Application Temperature		+5°C to +40°C
Base		Acrylic dispersion
Flow	ISO 7390	<2mm
Density	ISO 1183-1	1.56 g/ml
Elongation at Break	DIN 53505/ ISO 868	200%
Frost Resistance During Transportation		Down to -15°C
Tensile Strength	DIN 53504	0.52 N/mm ²
Skin Formation	DBTM 16	7 minutes @ +23°C/50% RH
Shore A Hardness	DIN 53505 / ISO 868	53
Temperature Resistance		-20°C to +75°C

These values are typical properties and may vary +/-3%

Shelf Life

In unopened original packaging between + 5°C and + 25°C, shelf life is up to 18 months from production date, stored in a dry place.

Certification

	EN 15651-1 F-EXT-INT
--	----------------------

Health & Safety

Safety data sheet (MSDS) must be read and understood before use of product. These are available on request.

