

**Product Code:** SCONTHMA300C

**Description:** Contractors General Purpose Silicone Adhesives Cartridge - Clear



## Benefits

- Versatile sealant
- High elasticity
- Good resistance to UV, water and weather

**Colour** Clear

## Application

Perimeter sealing around most types of door and window frames and seals glass to glass. Seals around pipes, sanitary fixtures and duct work.

## Directions Of Use

Cut the cartridge seal and screw on the nozzle which should be cut to your required size. Using a skeleton gun, apply the sealant into the gap ensuring a good solid fill. If required, place masking tape along edges, removing within 5 minutes of application. In deep joints reduce the joint depth to 50% of the joint width using expanding foam or joint backer rod.

## Limitations

Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates  
Not suitable for applications on concrete, marble, lead, copper and galvanized steel

## Paintability

This product is not paintable.

## Cleaning

Cured material can only be mechanically removed. Hands can be cleaned with SX Multi-Purpose Cleaning Wipes.

## Additional Information

100% Modulus	DIN 53504 S2	0.30 N/mm <sup>2</sup>
Application Rate	@ Ø3mm/6.3 bar	700 g/min
Application Temperature		+5°C to +40°C
Base		Acetoxy
Flow	ISO 7390	<2mm
Curing Time	+ 23°C / 50% RH	2mm/24 hours
Density	ISO 1183-1	0.96 g/ml
Elongation at Break	DIN 53504 S2	520%
Frost Resistance During Transportation		Down to -15°C
Tensile Strength	DIN 53504 S2	1.30 N/mm <sup>2</sup>
Skin Formation	DBTM 16	5 - 6 minutes @ + 23°C/50% RH
Shore A Hardness	DIN 53505	15
Temperature Resistance		-40°C to +180°C

These values are typical properties and may vary +/-3%

## Shelf Life

In unopened original packaging between + 5°C and + 25°C, shelf life is up to 18 months from production date, stored in a dry place.

## Health & Safety

Safety data sheet (MSDS) must be read and understood before use of product. These are available on request.

