

Product Code:

Technical Specification

SXSG50

Description: SX Trade Strength Superglue 50g



Benefits

- Bonds most rubbers and plastics such as PVCu
- Bonds rapidly at room temperature
- EVO-STIK Grip Filth Hand Wipes can also be used on tools and surfaces.

Application

Can be used to bond trims and caps on PVCu windows but can also bond most plastics, wood, plywood, leather, cork, most rubber, rubber foams, filled rubbers, ceramics and most metals.

Directions Of Use

Apply a small amount to one surface and assemble parts, holding for approximately 10-60 seconds. Cure speed is rapid so take care when aligning. Maximum strength is achieved in 24-48 hours.

Limitations

Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates

After skin contact immediately wash with lukewarm water and soap and rinse thoroughly.

Additional Information

Application Temperature	+5°C to +30°C
Base	Cyano-acrylic
Curing Time	3-30 seconds
Density	1.05 g/ml
Open Time	0-3 seconds
Tensile Strength	10 N/mm²
Viscosity	120 mPas

These values are typical properties and may vary +/-3%

Shelf Life

In unopened original packaging between + 5°C and + 25°C, shelf life is up to 12 months from production date, stored in a dry place.

Health & Safety

Safety data sheet (MSDS) must be read and understood before use of product. These are available on request.



