

Product Code: ZPBF1L

Technical Specification

Description: ZWALUW Instant Plaster Filler Tub - White



Benefits

- Ultra lightweight
- Almost non-shrinking
- Paintable with water based- and synthetic paints
- Sandable after curing
- Easy to apply
- Easy to clean
- Non corrosive towards metals

Colour White

Application

Zwaluw Plasterboard-Filler was specficially developed for filling one time joints and screw holes in plasterboard walls and ceilings for interior applications. Also for one time filling, repairing and smoothing of holes and cracks in concrete, plaster, brickwork and stucco layers.

Directions Of Use

For best results, the product should be applied without pressure.

Limitations

Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates
Not suitable for continuous exposure to water
Not suitable for movement joints

Paintability

Zwaluw Plasterboard-Filler is paintable when fully dry. During curing product will show minimal shrinkage, which can cause cracking of the paint. Paintable with water based and synthetic paints. Painting with highly water based paints can create cracking. We recoend testing compatability with paint prior to application.

Cleaning

Tools to be cleaned after use with water. Hands can be cleaned with Zwaluw Wipes and/or water and soap.

Additional Information

Shrinkage		<5%
Application Temperature		+5°C to +30°C
Base		Acrylic dispersion
Flow	ISO 7390	<2mm
Density		0,57 g/ml
Frost Resistance During Transportation		Down to -15°C
Skin Formation		5 Minutes @ +23°C/50% RH
Temperature Resistance		-20°C to +75°C

These values are typical properties and may vary $\pm -3\%$

